

FEATURES	APPLICATIONS
<ul style="list-style-type: none"> - ±20ppm (Frequency Stability) Available - Low Phase Noise and Jitter Performance - RoHS Compliant - Tape and Reel 	<ul style="list-style-type: none"> - High Definition TV - Avionics - Low Phase Signal Sources - Test and Measurement Equipment




PART NUMBERING GUIDE	
<p>SUNTSU VCXO → SVC F6 C 3 A 48 B 2 - 27.000M ← FREQUENCY (MHz)</p> <p>FR4 PCB 6 PAD →</p> <p>LVPECL →</p> <p>SUPPLY VOLTAGE 3: 3.3V±5% 5: 5.0V±5%</p> <p>FREQUENCY STABILITY A: ±50ppm B: ±30ppm C: ±25ppm *D: ±20ppm</p>	<p>TRI-STATE (ENABLE/ DISABLE) BLANK: NO CONNECTION 2: Pin 2</p> <p>PULLABILITY A: ±150ppm B: ±100ppm C: ±50ppm</p> <p>OPERATING TEMPERATURE RANGE 07: 0°C to +70°C 16: -10°C to +60°C 17: -10°C to +70°C 27: -20°C to +70°C 38: -30°C to +85°C 48: -40°C to +85°C</p>



Cage Code: 4GUT4
To customize your parameters contact a Suntsu representative.
* For frequency stability option D contact a Suntsu representative.

ELECTRICAL PARAMETERS	UNITS	MIN.	TYP.	MAX.	REMARKS
Frequency Range	MHz	10		800	
Frequency Stability (Includes Initial Tolerance at 25°C, Frequency Stability over Operating Temperature, Output Load Change, Supply Voltage Change, and First Year Aging at 25°C.)	ppm	-25		+25	See part numbering guide for options.
Operating Temperature	°C	-40		+85	See part numbering guide for options.
Storage Temperature	°C	-45		+90	
Supply Voltage (V _{DD})	3.3V Option	3.135	3.3	3.465	
	5.0V Option	4.750	5.0	5.250	
Current (I _{DD})	3.3V Option			70	
	5.0V Option			100	
Control Voltage (V _C)	3.3V Option	0.15		3.15	
	5.0V Option	0.0		5.0	
Pullability	ppm	±50		±100	See part numbering guide for options.
Input Impedance	kΩ			51	
Modulation Bandwidth	kHz	10			@-3dB.
Linearity	%			10	
Output Load (LVPECL)	Ω			50	50 Ω into V _{DD} -2.0V _{DC} .
Output Logic Levels	Output Logic High (V _{OH})	V _{DD} -1.025			
	Output Logic Low (V _{OL})			V _{DD} -1.620	
Rise (T _R) and Fall (T _F) Time	ns			1	Measured at 20% to 80% of Waveform.
Tri-State Input Voltage	Enable	0.7*V _{DD}			No Connection.
	Disable			0.3*V _{DD}	
Symmetry (Duty Cycle)	%	45	50	55	
Start-Up Time	ms			10	
Phase Jitter (12kHz ~ 20MHz)	ps			1	



OUTLINE DRAWING															
	<p>RECOMMENDED LAND PATTERN</p>														
<p>NOTE: Dimensions in millimeters (mm).</p>	<table border="1"> <thead> <tr> <th>PIN</th> <th>FUNCTION</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>VOLTAGE CONTROL</td> </tr> <tr> <td>2</td> <td>TRI-STATE or NC</td> </tr> <tr> <td>3</td> <td>GND</td> </tr> <tr> <td>4</td> <td>OUTPUT</td> </tr> <tr> <td>5</td> <td>COMP OUTPUT</td> </tr> <tr> <td>6</td> <td>V_{DD}</td> </tr> </tbody> </table>	PIN	FUNCTION	1	VOLTAGE CONTROL	2	TRI-STATE or NC	3	GND	4	OUTPUT	5	COMP OUTPUT	6	V _{DD}
PIN	FUNCTION														
1	VOLTAGE CONTROL														
2	TRI-STATE or NC														
3	GND														
4	OUTPUT														
5	COMP OUTPUT														
6	V _{DD}														



TYPICAL PHASE NOISE PERFORMANCE (MEASURED BY AGILENT E5052A)




TYPICAL JITTER PERFORMANCE (MEASURED BY AGILENT E5052A)




ENVIRONMENTAL & MECHANICAL SPECIFICATIONS

Temperature Cycling	MIL-STD-883, Method 1010, Condition B
Fine Leak Test	MIL-STD-883, Method 1014, Condition A
Gross Leak Test	MIL-STD-883, Method 1014, Condition C
Mechanical Shock	MIL-STD-883, Method 2002, Condition B
Vibration	MIL-STD-883, Method 2007, Condition A
Moisture Resistance	MIL-STD-883, Method 1004
Moisture Sensitivity	J-STD-020, MSL 1
Resistance to Soldering Heat	MIL-STD-202, Method 210, Condition K
Resistance to Solvents	MIL-STD-202, Method 215
Solderability	MIL-STD-883, Method 2003

REFLOW PROFILE




MARKING



TAPE AND REEL DIMENSIONS

500pcs/reel



NOTE: Dimensions in millimeters (mm); drawing is not to scale.