

FEATURES	APPLICATIONS
<ul style="list-style-type: none"> - $\pm 10\text{ppm}/\pm 10\text{ppm}$ (Tolerance/Stability) Available - Ultra-Miniature Package - AT-Cut Fundamental - RoHS Compliant - Tape and Reel 	<ul style="list-style-type: none"> - Bluetooth - Wireless LAN - High Density Applications



PART NUMBERING GUIDE

SUNTSU CRYSTAL → **SXT 10 4 10 A A 48 - 40.000M** ← **FREQUENCY (MHz)**

<p>1.2mm x 1.0mm</p> <p>4 PAD</p> <p>LOAD CAPACITANCE 5 - 10: 5pF - 10pF</p> <p>FREQUENCY TOLERANCE A: $\pm 50\text{ppm}$ B: $\pm 30\text{ppm}$ C: $\pm 25\text{ppm}$ D: $\pm 20\text{ppm}$ E: $\pm 15\text{ppm}$ F: $\pm 10\text{ppm}$</p>	<p>OPERATING TEMPERATURE RANGE 07: 0°C to + 70°C 16: -10°C to + 60°C 17: -10°C to + 70°C 27: -20°C to + 70°C 38: -30°C to + 85°C 48: -40°C to + 85°C</p> <p>FREQUENCY STABILITY A: $\pm 50\text{ppm}$ B: $\pm 30\text{ppm}$ C: $\pm 25\text{ppm}$ D: $\pm 20\text{ppm}$ E: $\pm 15\text{ppm}$ F: $\pm 10\text{ppm}^*$</p>
-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Cage Code: 4GUT4
To customize your parameters contact a Suntsu representative.
* For frequency stability option F contact a Suntsu representative.

ELECTRICAL PARAMETERS		UNITS	MIN.	TYP.	MAX.	REMARKS
Frequency Range		MHz	36		80	AT-Cut Fundamental.
Frequency Tolerance at +25°C		ppm	-10		+10	See part numbering guide for options.
Frequency Stability vs. Operating Temperature (Ref. 25°C) vs. Aging		ppm	-10		+10	See part numbering guide for options.
			-2		2	First year @ +25°C.
Operating Temperature		°C	-40		+85	See part numbering guide for options.
Storage Temperature		°C	-40		+125	
Load Capacitance		pF	5		12	See part numbering guide for options.
Shunt Capacitance		pF			5	
Drive Level		μW		10	100	
Insulation Resistance		M Ω	500			@ 100V _{DC} \pm 15V.
Equivalent Series Resistance	36.000MHz ~ 39.999MHz	Ω			150	AT-Cut Fundamental.
	40.000MHz ~ 47.999MHz				80	AT-Cut Fundamental.
	48.000MHz ~ 80.000MHz				60	AT-Cut Fundamental.

OUTLINE DRAWING

ELECTRODE ARRANGEMENT (BOTTOM VIEW)

RECOMMENDED LAND PATTERN

NOTE: Dimensions in millimeters (mm).

ENVIRONMENTAL & MECHANICAL SPECIFICATIONS	
Temperature Cycling	MIL-STD-883, Method 1010, Condition B
Fine Leak Test	MIL-STD-883, Method 1014, Condition A
Gross Leak Test	MIL-STD-883, Method 1014, Condition C
Mechanical Shock	MIL-STD-883, Method 2002, Condition B
Vibration	MIL-STD-883, Method 2007, Condition A
Moisture Resistance	MIL-STD-883, Method 1004
Moisture Sensitivity	J-STD-020, MSL 1
Resistance to Soldering Heat	MIL-STD-202, Method 210, Condition K
Resistance to Solvents	MIL-STD-202, Method 215
Solderability	MIL-STD-883, Method 2003

